



US008331554B2

(12) **United States Patent**
Oliver

(10) **Patent No.:** **US 8,331,554 B2**
(45) **Date of Patent:** ***Dec. 11, 2012**

(54) **METHOD FOR PIVOTABLY ADJUSTING A FIRST PORTION OF A DEVICE IN TWO DIRECTIONS RELATIVE TO A SECOND PORTION OF THE DEVICE**

4,594,750 A 6/1986 Carcas
4,747,122 A 5/1988 Bhagat et al.
5,168,221 A 12/1992 Houston
5,189,632 A 2/1993 Paajanen et al.
5,274,882 A 1/1994 Persson

(Continued)

(75) Inventor: **Mark W Oliver**, Fox River Grove, IL (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Motorola Mobility LLC**, Libertyville, IL (US)

EP 1429524 B1 4/2006
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 303 days.

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Motorola, Inc., "Motorola MPx one of First to Utilize New Windows Mobile 2003 Second Edition Software", http://www.motorola.com/mediacenter/news/detailpf/0,,4034_3395_23,00.html, Mar. 24, 2004, 2 pages, San Francisco.

(21) Appl. No.: **12/341,109**

(22) Filed: **Dec. 22, 2008**

Prior Publication Data

US 2009/0100642 A1 Apr. 23, 2009

Primary Examiner — Fan Tsang

Assistant Examiner — Phylesha Dabney

(74) *Attorney, Agent, or Firm* — Sylvia Chen; Keith J. Murphy

Related U.S. Application Data

(62) Division of application No. 11/027,177, filed on Dec. 30, 2004, now Pat. No. 7,499,540.

Int. Cl.

H04M 1/00 (2006.01)

H04M 9/00 (2006.01)

(52) **U.S. Cl.** 379/433.13; 455/575.3

(58) **Field of Classification Search** 379/433.13; 455/90.3, 550.1, 575.1, 575.3; 16/221, 223, 16/229–232, 242–243, 303, 319, 330, 366–367
See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

872,694 A 12/1907 Thiem
4,086,519 A 4/1978 Persson

(57)

ABSTRACT

A method for pivotably adjusting a first portion of a device in two directions relative to a second portion of the device includes: rotating the first portion relative to the second portion, about a first pivoting axis of a biaxially pivotable hinge and a uniaxially pivotable hinge, to be in a closed position (or a first open position) whereby the uniaxially pivotable hinge automatically deepens engagement when opened about the first pivoting axis; and rotating the first portion relative to the second portion about a second pivoting axis of the biaxially pivotable hinge to be in the closed position (or a second open position) whereby urging of the first portion relative to the second portion causes automatic disengagement of the uniaxially pivotable hinge.

2 Claims, 8 Drawing Sheets

